

# PP KOMPRESIONE SPOJNICE - 10 BARA

Prečnik Ø20 – Ø63 mm – Pritisak PN 10 bar

## PODRUČJE UPOTREBE

Navodnjavanje - uspostavlja mehanički spoj između polietilen (PE) cevi pod zemljom.

## MATERIJALI

Telo: crni Polipropilen (PP)  
Kapa: zeleni polipropilen (PP)  
Sigurnosni prsten: poliacetal (POM)  
Uvodnik: crni polipropilen (PP)  
Zaptivak: guma (NBR)  
Metalni prsten: nerđajući čelik (AISI 430)

## DOSTUPNI PREČNICI

Ø20 – Ø63 mm

## DOZVOLJENI RADNI PRITISAK

10 bara

04500



Spojnica sa vanjskim navojem PN10

04510



Spojnica sa unutrašnjim navojem PN10

04540



Završni element PN10

04520



Egal spojnica PN10

04530



Reducir spojnica PN10

05120



Obujmice

04570



Lakat spojnica PN10

04550



Lakat spojnica sa vanjskim navojem PN10

04560



Lakat spojnica sa unutrašnjim navojem PN10

04600



"T" spojnica PN10

04580




"T" spojnica sa vanjskim navojem PN10

04590



"T" spojnica sa unutrašnjim navojem PN10

## Uputstvo za montažu obujmice (opširnije na našem sajtu)



- 1 - Namestiti gumeni zaptivač
- 2 - Položiti obujmicu na cev
- 3 - Stegnuti šrafove
- 4 - Probušiti cev
- 5 - Za zaptivanje navoja koristiti teflon traku

## Uputstvo za montažu spojnice PN10 (opširnije na našem sajtu)



- 1 - Preseci i očistiti kraj cevi
- 2 - Navući na cev kapu pa zaptivni prsten
- 3 - Utisnuti cev u telo spojnice do graničnika
- 4 - Navući zaptivni prsten sa kapom i snažno zategnuti putem navoja
- 5 - Za zaptivanje navoja koristiti teflon traku